



# White Out

## Technical Specifications

### Total Solar Energy:

Transmitted % .....	20.0
Reflected % .....	46.0
Absorbed % .....	34.0

### Visible Light:


Transmitted % .....	15.0
Reflected Exterior % .....	61.0
Reflected Interior % .....	78.0
Glare Reduction % .....	84.0

Solar Heat Gain Coefficient .....	0.30
Shading Coefficient .....	0.35
Luminous Efficacy .....	0.42
Total Solar Energy Rejection % .....	70.0
Infrared Rejection %* .....	73.0

U Factor .....	1.04
Emissivity .....	0.87
Ultraviolet Rejection % .....	95.0

\* Near IR range (780-2500nm)  
 Technical specification definitions can be found at  
[www.madico.com](http://www.madico.com)

Read in accordance with National Fenestration Rating  
 Council (NFRC) standards on 3mm clear glass.



### Specification Use Statement

Reported values are typical properties and should not be used as a specification. Since the user is aware of the specific conditions in which the product is to be used, it is the user's responsibility to determine whether the product is suitable for intended use. If you need verification regarding specific use or additional information, please contact Madico Window Films or your local Madico Authorized Dealer.



## White Out

White Out can be used to increase privacy or for decorative design applications in office buildings, restaurants, retail environments and other places where you may want to alter the opacity of glass.

### Product Benefits

- Cuts Glare
- Increases Privacy
- Reduces Heat Gain
- Helps Shatter Resistance
- Rejects 95% of UV Rays
- Slows Fading of Furnishings, Flooring

### *Why Sun-Gard?*

Sun-Gard window films are an elegant, practical solution for comfort, protection and natural appearance. Enjoy your view by embracing sunlight while minimizing the negative effects of the sun such as glare, harmful ultraviolet exposure and unwanted heat. Sun-Gard films are installed by professionals and backed by a manufacturer's warranty.

[www.sun-gard.com](http://www.sun-gard.com)

